



Axle cross-section (mm)	Track width SP (mm)	Spring centre FM (mm)	Ride height (mm)	Axle load (kg)		BPW code number
				40 km/h	60 km/h	

Rigid axle: GSOH 11010-1 - axle load up to 9,000 kg (60 km/h)

Brake FL4112 410 x 120 mm - wheel connection 280/335/10 ET 0 - M22 x 1.5

120 x 15	1,950	750	351	10,000	9,000	56.88.08.0600
120 x 15	2,000	750	351	10,000	9,000	56.88.08.0601
120 x 15	2,050	750	351	10,000	9,000	56.88.08.0602
120 x 15	2,100	850	351	10,000	9,000	56.88.08.0603
120 x 15	2,150	850	351	10,000	9,000	56.88.08.0604
120 x 15	2,225	850	351	10,000	9,000	56.88.08.0605

Steering axle: GSOHLA 11010-1 - axle load up to 9,000 kg (60 km/h)

Brake FL4112 410 x 120 mm - wheel connection 280/335/10 ET 0 - M22 x 1.5

120 x 15	1,950	650	351	10,000	9,000	56.88.08.0606
120 x 15	2,000	650	351	10,000	9,000	56.88.08.0607
120 x 15	2,050	750	351	10,000	9,000	56.88.08.0608
120 x 15	2,100	750	351	10,000	9,000	56.88.08.0609
120 x 15	2,150	850	351	10,000	9,000	56.88.08.0610
120 x 15	2,225	850	351	10,000	9,000	56.88.08.0611

Rigid axle: GSOH 12010 - axle load up to 12,000 kg (40 km/h)

Brake FL4118 410 x 180 mm - wheel connection 280/335/10 ET 0 - M22 x 1.5

150 x 16	1,950	750	371	12,000	11,000	56.72.08.0600
150 x 16	2,000	750	371	12,000	11,000	56.72.08.0601
150 x 16	2,050	750	371	12,000	11,000	56.72.08.0602
150 x 16	2,100	850	371	12,000	11,000	56.72.08.0603
150 x 16	2,150	850	371	12,000	11,000	56.72.08.0604
150 x 16	2,225	850	371	12,000	11,000	56.72.08.0605

Steering axle: GSOHLL 12010 - axle load up to 12,000 kg (40 km/h)

Brake FL4118 410 x 180 mm - wheel connection 280/335/10 ET 0 - M22 x 1.5

150 x 16	1,950	650	365	12,000	11,000	56.72.08.0606
150 x 16	2,000	650	365	12,000	11,000	56.72.08.0607
150 x 16	2,050	750	365	12,000	11,000	56.72.08.0608
150 x 16	2,100	750	365	12,000	11,000	56.72.08.0609
150 x 16	2,150	850	365	12,000	11,000	56.72.08.0610
150 x 16	2,225	850	365	12,000	11,000	56.72.08.0611

Version GSOH (L..) also available for 80 km/h.

Steering axles with cast steel steering housing have an axle load of 13,000 kg.

Strongly recommended for axle modules in a tri-axle suspension.

All suspension units are also available with axle type GS 14010.