



Axle cross-section (mm)	Track width SP (mm)	Spring centre FM (mm)	Axle load			BPW code number
			40 km/h	60 km/h	80 km/h	

GS LA 11010-1 - axle load up to 10,500 kg (40 km/h)
Brake FL4112 410 x 120 mm - wheel connection 280/335/10 ET 0 - M22 x 1.5

120 x 15	1,950	850	10,500	10,000	-	36.88.460.900
120 x 15	2,000	900	10,500	10,000	-	36.88.460.901
120 x 15	2,050	950	10,500	10,000	-	36.88.460.902
120 x 15	2,100	1,000	10,500	10,000	-	36.88.460.903
120 x 15	2,150	1,050	10,500	10,000	-	36.88.460.904
120 x 15	2,225	1,100	10,500	10,000	-	36.88.460.905

GS(H)LL 12010 - axle load up to 13,000 kg (40 km/h)
Brake FL4118 410 x 180 mm - wheel connection 280/335/10 ET 0 - M22 x 1.5

150 x 16	1,950	850	13,000	12,000	-	26.72.449.600
150 x 16	2,000	900	13,000	12,000	-	26.72.449.601
150 x 16	2,050	950	13,000	12,000	-	26.72.449.602
150 x 16	2,100	1,000	13,000	12,000	-	26.72.449.603
150 x 16	2,150	1,050	13,000	12,000	-	26.72.449.604
150 x 16	2,225	1,100	13,000	12,000	-	26.72.449.605

GS(H)LL 14010 - axle load up to 15,000 kg (40 km/h)
Brake FL4118 410x180 mm - wheel connection 280/335/10 ET 0 - M22 x 1.5

150 x 16	1,950	850	15,000	14,000	-	36.74.449.600
150 x 20	1,950	600	15,000	14,000	-	36.74.449.601
150 x 16	2,000	900	15,000	14,000	-	36.74.449.602
150 x 20	2,000	650	15,000	14,000	-	36.74.449.603
150 x 16	2,050	950	15,000	14,000	-	36.74.449.604
150 x 20	2,050	700	15,000	14,000	-	36.74.449.605
150 x 16	2,100	1,000	15,000	14,000	-	36.74.449.606
150 x 20	2,100	750	15,000	14,000	-	36.74.449.607
150 x 16	2,150	1,050	15,000	14,000	-	36.74.449.608
150 x 20	2,150	800	15,000	14,000	-	36.74.449.609

GSNLL 12010 - axle load up to 12,000 kg (80 km/h)
Brake SN4220 420 x 200 mm - wheel connection 280/335/10 ET 0 - M22 x 1.5

150 x 16	1,950	800	-	-	12,000	36.72.744.600
150 x 16	2,000	900	-	-	12,000	36.72.744.601
150 x 16	2,050	950	-	-	12,000	36.72.744.602
150 x 16	2,100	1,000	-	-	12,000	36.72.744.603
150 x 16	2,150	1,050	-	-	12,000	36.72.744.604
150 x 16	2,225	1,100	-	-	12,000	36.72.744.605

Version GS LA is also available with 8-hole wheel connection.
 The specified spring centres depend on the track width and the tyres.
 Standard delivery state for positive steering.
 Installation parts kit for self-steering is available as an option.